VelocityReport Plugin - Feature #484

Allow override of default Cache-Control & Expires HTTP header

04/03/2012 06:40 PM - Ryan Parrish

Status: Closed Start date: 04/03/2012

Priority: Normal Due date:

Assignee: % Done: 0%

Category: velocity Estimated time: 0.00 hour

Target version: v2.0

Browser (if web

client):

Description

I feel the default provided Cache-Control & Expires HTTP headers of

Cache-Control: \max -age=0, \max -revalidate, proxy-revalidate Expires: 0

work fine in most use cases, however if a programer wants to adjust them, they cannot.

If we attempt to do the following...

ResponseObject.addHeader('Cache-Control', "max-age=86400, public, no-cache, must-revalidate");

The HTTP header will come back with our string concatenated to the end of the default (which I'm unsure if this is a valid header anymore).

Cache-Control: max-age=0, must-revalidate, proxy-revalidate, max-age=86400, public, no-cache, must-revalidate

So I would propose that if the programer tries to set a HTTP header that already has a default defined in the plugin that you simply overwrite the default value with the programer defined one.

History

#1 - 04/03/2012 07:01 PM - Patrick Talbot

- Status changed from New to Closed

You are right. Next version will allow users to set these headers explicitely. If not set, the defaults will be used.

04/27/2025 1/1